

J. B. Jewitt Co., Inc.
Homestead Finishing Products
 1935 West 96th Street Unit Q
 Cleveland OH 44102-2673
 Telephone: (216) 631-5309

Emergency Assistance

For emergency assistance involving this product call – 216-631-5309

Section 1: Product Identification
--

Product Name: TransTint® 6010 Red Mahogany
MSDS #: 6010
Date Issued: December 5, 2006
Original **Update**
Reason For Change: Revised formula, general regulatory update

Section 2: Hazardous Ingredients

Hazardous Ingredients	CAS Number	OSHA PEL (Permissible exposure limit)	ACGIH TLV (Threshold limit value)	% By Weight	EU Symbol/ Classifications
Diethylene glycol monobutyl ether	112-34-5	Not established	Not established	20-30	XI; R36
2-Propoxyethanol	2807-30-9	Not established	Not established	20-30	XN; R21/R36
Proprietary dye compound	NA	Not established	Not established	10-20	Not classified
Proprietary chromium complex (Cr ⁺³) compounds	NA	Not established	Not established	10-15	Not classified
2-Propanol, 1-methoxy	107-98-2	100 ppm	369 mg/m ³	5-10	R10
1,2-Propanediol	57-55-6	Not established	Not established	1-5	Not classified
2- Furanmethanol, tetrahydro	97-99-4	Not established	Not established	1-5	XI; R36

* TWA = Time weighted average, STEL= Short Term Exposure Limit

Note: All health hazard components above 1% composition and all carcinogens above 0.1% (1000 ppm) composition are listed.

Section 3: Hazard Identification

EMERGENCY OVERVIEW: WARNING! This product is HAZARDOUS by OSHA Hazard Communication definition. May cause skin, eye and respiratory tract irritation. May be harmful if inhaled, absorbed through the skin or swallowed. Excessive exposures may cause central nervous system disorders and produce anesthetic or narcotic effects. May cause blood disorders.

Hazard Rating: NFPA
Health: *2

HMIS

Hazard Rating Scale:
0= Minimal

Blood, eyes, respiratory system, skin, eyes and central nervous system

The components of this material are considered Carcinogenic by:

Not Known

National Toxicology Program (NTP)

The International Agency for Research on Cancer (IARC)

The Occupational Health and Safety Administration (OSHA)

Section 4: First Aid Measures

Eye Contact.....	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, holding eyelids open to rinse completely. Get medical aid.
Ingestion.....	If swallowed, give 3-4 glasses of water but do not induce vomiting. If vomiting occurs, give water again. Never give anything by mouth to an unconscious person. Potential for aspiration if swallowed. Get medical aid immediately. Have physician determine whether vomiting or stomach evacuation is necessary.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.
Skin Contact.....	In case of contact, flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical aid if irritation, redness, swelling or skin pain develops and persists. Wash clothing before re-use.
** Note to the Physician:.....	None.

Section 5: Fire Fighting Measures

Flash Point Deg. C <input type="checkbox"/> F <input checked="" type="checkbox"/>	>141 degrees
Auto – Ignition Temperature.....	Not determined
Upper Flammable Limit (% Vol).....	Not determined
Lower Flammable Limit (% Vol).....	Not determined
Extinguishing Media.....	Use water fog, dry chemical, carbon dioxide or foam. Cool containers with water until well after the fire is out.
Hazardous Combustion Products.....	Oxides of carbon, nitrogen and other toxic vapors

General Information:

Firefighters should wear full protective equipment and positive pressure self-contained breathing apparatus in pressure-demand mode. Vapors may form an explosive mixture with air. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low areas. Use water spray to cool fire-exposed container surfaces.

Section 6: Accidental Release Measures

Spill / Leak.....	Use proper personal protective equipment as indicated in Section 8. Stop flow of material. Absorb with inert material (e.g. dry sand, earth or other suitable absorbent), then place into a suitable container. Clean up spills immediately. Provide ventilation. Remove all sources of ignition. Use a spark-proof tool. Prevent from entering floor drains or sewers. Do not release any chemicals, dyes, or dye solutions of any type to sewers or any waterways without proper authorization from government agencies. Make appropriate notifications as required.
-------------------	--

Hazardous Polymerization.....	Will not occur
Stability.....	Stable
Incompatibility.....	Strong oxidizing agents, strong acids, strong bases
Conditions to Avoid.....	Ignition sources, excess heat
Hazardous Products of Decomposition.....	Oxides of carbon and nitrogen and other toxic vapors

Section 11: Toxicology Information

Irritancy of Material.....	May cause skin, eye and respiratory irritation.
Sensitizing Capability of Material.....	Not determined
Carcinogenicity of Material.....	See Section 3
Teratogenicity	Not known
Mutagenicity.....	Not known
Reproductive Effects.....	For 2-Propanol, 1-methoxy (CAS# 107-98-2): (Rats, Mice and Rabbits): Exposure to 0.04 to 2 mg/kg/day during the first 18-21 days of gestation were found to cause no effects in mice and rabbits; delayed ossification was seen in the rat. (Rats): Inhalation of 3000 ppm for 6 hrs/day on day 6-15 of pregnancy was found to cause delayed ossification in offspring. Reproductive Effects (Rats and Rabbits): Inhalation Exposure to male rats and rabbits of 300, 1000 or 3000 ppm 6 hrs/day, 5-days/week for 13 weeks did not show evidence of testicular effects. For 2-Propoxy ethanol (CAS# 2807-30-9): (Rats): Inhalation of 400 ppm of 6 hrs/day on day 6-15 of pregnancy was found to cause musculoskeletal system defects in offspring. (NTIS study) (Mice): Oral dose of 16 gm/kg on day 7-14 of pregnancy was found to cause stillbirth of offspring. (NTIS study)
Synergistic Materials.....	Not known

Section 12: Ecology Information

Environmental.....	Volatile and water-soluble.
Biodegradability.....	Should be biodegradable after an acclimation period. Not expected to be persistent or bioaccumulative. Avoid accidental release. 2-Propoxy ethanol (CAS# 2807-30-9) has a high biological oxygen demand (BOD) and a potential to cause oxygen depletion in aqueous systems. When diluted with a large quantity of water, it is not expected to have a significant impact when released in the environment

Section 13: Disposal Considerations

Waste Disposal	May be classified as a listed waste (D007, chromium) when disposed as supplied. Waste generators must consult with federal, state and local hazardous waste regulations to ensure complete and accurate classification.
----------------------	---

Section 14: Transport Information

U. N. #	NA 1993
D.O.T. Classification	Not regulated if transported by ground (Non-bulk) Combustible liquids, NOS (contains 2-propoxyethanol, 2-propano1-methoxy) 3, PG III (if shipped in containers >119 gallon)
IATA.....	Not regulated

Section 15: Regulatory Information

- | | |
|--|--|
| <input checked="" type="checkbox"/> TSCA | <input checked="" type="checkbox"/> Components of this product are listed on the TSCA Inventory or are exempt. |
| <input checked="" type="checkbox"/> CERCLA | <input checked="" type="checkbox"/> Glycol ether compounds: Listed, no RQ assigned
Chromium, chromium compounds: No RQ is assigned to this generic class of compounds, although the class is a CERCLA hazardous substance. |
| <input checked="" type="checkbox"/> SARA TITLE III | <input checked="" type="checkbox"/> This product is considered, under applicable definitions, to meet the following categories:
<u>Section 311/312:</u>
Immediate/acute health hazard
Delayed/chronic health hazard

<u>Section 313:</u>
This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under Section 313 (40 CFR 372). This information must be included in all MSDSs copied or distributed for this material:
2-Propoxyethanol (CAS# 2807-30-9)
Diethylene glycol monobutyl ether (CAS# 112-34-5)
Chromium compounds |
| <input type="checkbox"/> CALIFORNIA PROPOSITION 65 | <input checked="" type="checkbox"/> This product does not contain chemicals known to the state of California to cause cancer or reproductive toxicity. |
| <input checked="" type="checkbox"/> STATE RIGHT-TO-KNOW LISTING | <input checked="" type="checkbox"/> <u>California:</u>
None listed

<u>Florida:</u>
None listed

<u>Illinois:</u>
Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS# 34590-94-8)
2-Propanol, 1-methoxy (CAS# 107-98-2)

<u>Massachusetts:</u>
Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS# 34590-94-8)
2- Furanmethanol, tetrahydro (CAS# 97-99-4)
2-Propanol, 1-methoxy (CAS# 107-98-2)

<u>Minnesota:</u>
Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS# 34590-94-8)
2-Propanol, 1-methoxy (CAS# 107-98-2)

<u>New Jersey:</u>
Ethanol, 2-propoxy- (CAS# 2807-30-9)
Propanol, 1(or 2)-(2-methoxymethylethoxy)- (CAS# 34590-94-8)
2-Propanol, 1-methoxy (CAS# 107-98-2) |

Pennsylvania:

Propanol, 1(or 2)-(2-methoxymethylethoxy)-
(CAS# 34590-94-8)

Ethanol, 2-propoxy- (CAS# 2807-30-9)

1,2-Propanediol (CAS# 57-55-6)

2- Furanmethanol, tetrahydro (CAS# 97-99-4)

2-Propanol, 1-methoxy (CAS# 107-98-2)

Rhode Island:

1,2-Propanediol (CAS# 57-55-6)

2-Propanol, 1-methoxy (CAS# 107-98-2)

CANADA

Domestic Substances List:

Not determined

WHMIS classification:

Not determined

EUROPEAN INFORMATION

R21 Harmful

R36 Irritating to eyes

S7/S9 Keep container tightly closed and in a well-ventilated area

S24/S25 Avoid contact with skin and eyes

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin wash immediately with plenty of water

S36/S37/S39 Wear suitable protective clothing, gloves and eye protection

XI

Section 16: Other Information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. This information is based on the material as manufactured, it may not be valid for this material if used in combination with any other materials or in any process. J.B. Jewitt Co., Inc./Homestead Finishing Products shall not be held liable for any damage resulting from handling or from contact with the product(s).